

TP-701CC TECHNICAL DATA

Arch Size (mm):

TP-701CC-L 1650 x 500
TP-701CC-M 1250 x 500
TP-701CC-S 850 x 500

Minimum Packaging Size:

300 mm (L) x 200 (W) x 20 mm (H)

Strap Tension:

8-35 kg

Speed:

24 bundle/minute (single strap)
14 bundle/minute (double strap)
(Model: TP-701CC-L / 1650 x 500)

Strap Width:

5mm, 6mm and 9 mm

Power:

110V, 220V, 230V, 380V, 400V, 480V, 575V
50/60Hz 1PH or 3PH

TP-701CC



FULLY AUTOMATIC CORRUGATED STRAPPER

Providing the most cost effective solution for the corrugated industry.

The TP-701CC has 30% fewer parts than comparable strappers, requires fewer adjustments and less maintenance and has fewer wear components. The simple design makes maintenance and training far easier than other strappers.

OPTIONS

- Light tree alarm (dual lamp)
- Operator friendly low strap sensor (triple lamp)
- Safety guards




SIEMENS PLC CONTROL



LCD DISPLAY



HINGED TOP PLATES



Opens fully for quick cleaning, inspection and maintenance of strapping head, strap-feed and tensioning unit.

ONE-PIECE STRAP CHUTE




Utilizing a highly reliable one-piece strap chute from a low-wear, low-friction material, the strap chute opens automatically when malfunction occurs.

WAIST-HIGH AUTO STRAP FEEDING



Designed to feed the strap automatically from the upper side of coil without access to the bottom of the machine.

COMPACT MECHANICAL STRAPPING HEAD



The corrugated strapper uses the latest multi DC brushless motor technology provides "the highest level of accuracy currently available in the strapper industry."

User Friendly. With HMI touch panel for operating instructions, adjustments and troubleshooting guide.

Mikah Thorne

Progressive Systems & Packaging

2841 Langstaff Rd., Unit 1B • Concord • Ontario • L4K 4W7

P. 647-237-6756

mikah@prosypack.ca

